NIKA SALES
GUELPH · ONTARIO

AUTHORIZED DEALER

Dustbane Products Ltd. · Canadian cleaning solutions since 1908

20″ WALK-BEHIND AUTO-SCRUBBER · TRACTION DRIVE

Hurricane 400 XTT Traction

Dustbane Hurricane 400 XTT-TR, complete with AGM batteries

Dustbane code **19319-TR-C-AGM** · base model **19319-TR**



A compact battery scrubber that drives itself, so the operator steers instead of pushing. It scrubs and dries in one pass, with 40 L of solution in a 20″-wide body.

- **Less push, more floor.** A powered drive with variable speed up to 4.2 km/h lifts Dustbane's productivity rating 29% over the push model.
- **Quiet enough to run while you're open.** 67 dB, so it can work in occupied offices, schools and care homes.
- **Leaves the floor dry and safe to walk on.** The 32″ squeegee is wider than the 20″ path, and a 2-stage vacuum motor pulls 48″ of water lift.
- **Low upkeep.** Sealed AGM batteries mean no watering, and the on-board charger lets you charge it right where it's parked.

20″	9.6k–13.1k	10.6 gal	2.2 h	161 lb
51 cm single brush	ft²/h, est. real-world	40 L solution · 50 L recovery	2 × 12 V 110 Ah AGM	73 kg, without batteries
CLEANING PATH	PRACTICAL OUTPUT	SOLUTION TANK	RUN TIME	MACHINE WEIGHT

BUILT FOR THE WORK



Single 20″ brush deck

155 rpm on a 600 W brush motor. Solution feeds from the brush centre, so it lands where the pad is working, not ahead of it.



32″ squeegee

81.5 cm wide, so it dries past both edges of the scrub path. Blades flip to use all four edges before you replace them.



Big tanks, small footprint

40 L of solution and a 50 L recovery tank in a 48″ × 20″ body. That means fewer trips to the sink on a long floor.

TRACTION VS PUSH: WHAT CHANGES

Same 20″ deck, tanks and squeegee. The difference is the drive.

	PRODUCTIVITY RATING	TOP SPEED	RUN TIME
	24,219 ft²/h	**4.2 km/h**	**2.2 h**
	vs 18,836 for the push 400 XTT (+29%)	2.6 mph, set on a dial. The push model goes as fast as you walk.	vs 2.5 h push. The drive motor uses about 18 min of battery.

WHERE IT FITS

Schools
Corridors, classrooms and cafeterias between bells

Offices & government
Lobbies and hallways during occupied hours

Health & senior care
Quiet daytime scrubbing in common areas

Retail & showrooms
Dealership floors, aisles and back-of-house

Recreation
Arena concourses, change rooms and lobbies

Book a demo on your own floor.

We'll bring the Hurricane 400 XTT – Traction to your site and run it on your floors.

(519) 824-0620 · toll-free (888) 250-8721
sales@nikasales.ca · nikasales.ca
40 Taggart St #5, Guelph, ON N1L 1M5 · Mon–Fri 8:30–5:00

Specifications are from Dustbane Products Ltd. literature (product page and spec sheet). **Productivity**: 24,219 ft²/h is Dustbane's theoretical rating at maximum speed. Real coverage depends on soil load, floor layout and operator. The practical estimate is a Nika Sales calculation: 0.51 m path × 2,500–3,000 m/h × 70–80% efficiency. The photo shows the Hurricane 400 XTT range, and controls on the traction model may differ. Full specifications are on page 2. Specifications are subject to change without notice.

NIKA

Dustbane Hurricane 400 XTT – Traction · 19319-TR-C-AGM

Technical specifications & ordering guide

SPECIFICATIONS

HURRICANE 400 XTT – TRACTION (19319-TR)	
PERFORMANCE	
Productivity (theoretical)	**24,219 ft²/h (2,250 m²/h)**
Practical coverage (est.)	**≈ 9,600–13,100 ft²/h (890–1,220 m²/h)**
Scrubbing width	**20″ (51 cm)**
Squeegee width	**32″ (81.5 cm)**
Drive / maximum speed	**Traction motor, variable, 4.2 km/h (2.6 mph)**
SCRUB & RECOVERY	
Brush / pad	**1 × 20″ (51 cm), 155 rpm**
Brush motor	**600 W**
Vacuum motor	**2-stage, 480 W**
Water lift at squeegee	**48″ (123 cm)**
TANKS & POWER	
Solution / recovery tank	**10.6 / 13.2 US gal (40 / 50 L)**
Batteries	**24 V: 2 × 12 V 110 Ah AGM, sealed**
Charger	**On-board, 24 V / 15 A**
Run time	**2.2 h**
MACHINE	
Weight (without batteries)	**161 lb (73 kg)**
Body size L × W × H	**48 × 20 × 38″ (122 × 51 × 97 cm)**
Noise level	**67 dB**
Operating temperature	**4 – 35 °C (39 – 95 °F)**

Supplied with

- 2 × 12 V 110 Ah AGM batteries, installed
- 24 V / 15 A on-board charger
- 20″ pad driver
- 32″ squeegee with HD latex blades, front and rear
- Operator's manual

This is the "complete AGM" package (-C-AGM). We confirm the exact package contents on your quote.

Why AGM batteries

They are sealed, so there's no watering, no acid checks and no spill risk in the battery bay. Charge them after each shift and let the charger finish its cycle (green light). Dustbane advises against cutting a charge short.

Quiet enough for daytime cleaning

At 67 dB it runs about as loud as a normal conversation nearby, so you can scrub lobbies and corridors while people are using them instead of booking night shifts.

What it really covers

Dustbane's 24,219 ft²/h is the number at full speed in a straight line. Plan on ≈ 9,600–13,100 ft²/h once you add turns, refills and edges. A 40,000 ft² floor works out to about 3 to 4 hours of scrubbing. That's more than one battery charge, so plan for a mid-job recharge or split the floor across two shifts.

DUSTBANE WARRANTY

3 yr	10 yr	1 yr	1 yr	90 days
Major electrical, brush & vac motors, transmission (or 2,000 h)	Tanks & housings: cracks and corrosion	Labour at an authorized service centre	Batteries & charger, pro-rated (genuine Dustbane AGM)	Travel, up to 3 hours

BEFORE YOU ORDER

- ☐ **Ramps.** Dustbane rates this machine for slopes of no more than 2%, and the drive motor doesn't change that. It isn't for parkade or loading-dock ramps.
- ☐ **Lifting & transport.** 161 lb is the dry weight. Two 110 Ah AGM batteries add a lot on top of that, so get the shipped weight before you plan a lift into a van.
- ☐ **Charging spot.** Set aside a place where it can sit plugged in overnight. The on-board charger needs a full, uninterrupted cycle.
- ☐ **Doorways & storage.** The body is 20″ wide but the squeegee is 32″. Measure the closet and any tight doorways with the squeegee on.
- ☐ **Cold spaces.** It's rated to operate between 4 and 35 °C and to be stored at 0 °C or warmer. Don't park it in an unheated warehouse or garage over a Canadian winter.
- ☐ **Oily floors?** Ask for oil-resistant urethane squeegee blades. Latex blades are the standard fit.

Questions, quotes or a demo?

Ask us about pads, blades and brushes for the Hurricane range.

(519) 824-0620 · toll-free (888) 250-8721
sales@nikasales.ca · nikasales.ca
40 Taggart St #5, Guelph, ON N1L 1M5 · Mon–Fri 8:30–5:00

Sources: Dustbane product page and Hurricane 400 XTT spec sheet (19319-TR), operations manual (rev. 2020-04), parts manual (rev. 2021-01), quick guide (400 TR) and Auto-Scrubber Warranty Policy, all retrieved October 2026. **Converted figures:** Dustbane prints the solution tank as "11 gal (40 L)" and the recovery tank as "13 gal (50 L)". The US-gallon figures shown here are converted from litres. Water lift appears as Dustbane publishes it. Body dimensions follow the spec sheet's L × W × H order and don't include the squeegee. Warranty terms follow Dustbane's policy: wear items (pads, brushes, blades, filters, hoses, etc.) aren't covered, and coverage depends on approval by Dustbane Technical Services. Specifications are subject to change. Nika Sales · Rev. 2026-10-13.